

# SHR 2000

## RAPID PALLET TRUCK

**BOLTS, SHAFTS AND AXLES MADE OF  
STAINLESS STEEL**



### HYDRAULIC SYSTEM

Fast lifting 2-speed hydraulic system with optimal force – distance transmission. To switch over from rapid to normal lifting is direct during the pumping process without extra drawbar running. 1 pumpage is enough to lift even loaded pallets and then to move them. Full lifting with only 3 ½ pump impulses in the fast lifting zone.

### REALIZATION

Steering rollers: all rubber wheels on aluminium rims. Steering angle: 240°. Load rollers: Single rollers made of polyamide or polyurethane with a steel core. All the wheels are fitted out with ball bearings, shafts fitted into casings that require no maintenance. Robust, robot welded chassis with high quality surface painted with coating powder (with no cadmium or heavy metal); colour yellow/blue.

### SPECIAL MODELS

Type SHR "Frosty" for cold stores  
Type SHR "Silent" with special sound deadening for use in inhabited areas  
Type SHR "Inox": all parts are made of stainless steel (including bearings). Special lengths and widths.

### STÖCKLIN – YOUR ADVANTAGES

Stöcklin rapid lifting:

- **Work faster thanks to optimal transmission**
- **No idle running during hydraulic level switch over**
- **Low energy consumption thanks to a long drawbar**
- **Minimal maintenance**

In use:

- **Optimum response at all times**
- **Long service life**
- **Low wear and tear on the shaft, bolts and main bearing etc.**
- **It is not a one-job machine - it is worth repairing**

### VALVE CARTRIDGE

The Stöcklin valve cartridge runs all the hydraulic functions such as fast lifting switch over and dosed lowering. No other small equipment is necessary in the hydraulic power pack. Maintenance work can even be carried out without oil change.

### ERGONOMY



After 50 years experience in building electric pallet trucks, we at Stöcklin know what our customers need. Geometry has constantly been refined, load distribution optimised. All the professionals confirm that the SHR 2000 is easy to handle, pleasant for the operator to drive which makes it easier to carry out the job in less time.

Stöcklin pallet trucks with a fast lifting device have been manufactured for over 30 years.

**Stöcklin**

# SHR 2000

## TECHNICAL DATA



Model	2008	2009	2010	2012
load capacity [kg]	2000	2000	2000	2000
length of fork L [mm]	800	900	1000	1150

Combinable widths				
width B [mm]	450	540	680	
width of fork e [mm]	145	160	160	
interior dimension b [mm]	160	220	360	

Special lengths from 500-3500 mm | Special widths on request

### Additional protection against corrosion:

- galvanised chassis
- parts in stainless steel

### Other models of pallet trucks

SHR 3000	fast lifting, load capacity 3000 kg
NHR 2000/3000	normal high quality lifting
SHR Scales	fast lifting with weighing system
Atex	protection against explosion zone 2G IIC T6

Subject to technical modifications.

### Additional equipment



- Additional safety:
- Blocking brake n° 2043 on lorry



- Wheel and blocking brake n° 2048 on slopes



- The right wheels:
- Single or tandem rollers made of polyamide, polyurethane or steel
  - Steering rollers made of rubber, polyamide, polyurethane or rubber to avoid skid marks.

Stöcklin, or its partners in your region, is at your service to advise you.

## Stöcklin

**Stöcklin Logistics Ltd.**  
Materials Handling and Storage Systems  
**CH-4143 Dornach**  
Tel. +41 (0) 61 705 81 11  
Fax +41 (0) 61 705 82 25  
E-Mail [unit-f@stoeklin.com](mailto:unit-f@stoeklin.com)  
[www.stoeklin.com](http://www.stoeklin.com)